MATERIAL SAFETY DATA SHEET

PRODUCT NAME: MAXIMA 100% ACRYLIC PAST.BASE HMIS CODES: H € R ₱ PRODUCT CODE: MAYES

MANUFACTURER'S NAME: Lanco Mito.

ADDRESS: URB. APUNTE #5 SAN EURENZU PK, WU754

EMERGENCY PHONE: 1-800-424-9300 INFORMATION PHONE: (787) /36-4221

DATE REVISED : พ.ศ. พ.ศ. พ.ศ. OF PREPARER : VICTUR M. HERNANDEZ

======= SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ========

MAZARDOUS COMPONENTS	űAS NUMBÉK		IONAL EXPOSU ACGIN TLV	RE LIMITS OTHER	VAPOR PRESSURE WELGHT am ng é TEMP PERCENT
whitek	7732-18-5	NVA	N\A	N\A	 N/A
MICROBICIDE	MIXTURE	.5 ug/u 3	N/A	N/A	N∕Ĥ
*B1UXIDE	MIXTURE	mg/m3	.3 mg/m3	N/H	ú.a∂ 0 î\0.5⊁

^{*} indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

======== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =========

BOILING POINT: N/H SPECIFIC GRAVITY (H2O=1): 1.
VAPOR DENSITY: LIGHTER THAN ATR EVAPORATION RATE: N/H
COATING V.O.C.: 1.27 LB/GL (153 B/L)
MATERIAL V.O.C.: 0.57 LB/GL (69 B/L)

SOLUBILITY IN WATER: AUGEBOUS SYSTEM

APPEARANCE AND ODOR:

----- SECTION IV - FIRE AND EXPLOSION HAZARD DATA -----

FLASH POINT: N/A METHOD USED: N/H
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/H

EXTINGUISHING MEDIA: , COZ, WATER FOR, WITHER

SPECIAL FIREFIGHTING PROCEDURES

SUMMON PROFESSIONAL FIREFIGHTERS. USE FULL PROTECTIVE EQUIPMENT INCLUDING SELFCONTAINED BREATHING APPARATUS. WATER SPRAY MAY BEINEFFECTIVE. IF WATER IS USED, FORNOZZLES ARE PREFERABLE.

UNUSUAL FIRE AND EXPLOSION HAZARDS

DUE TO PRESSURE BUILD- UP, DLOSED CONTAINERS EXPOSED TO EXTREME MEAT MAY EXPLODEDURING EMERGENCY CONDITIONS, OVEREXP— SURE TO DECOMPOSITION PRODUCT MAY CAUSE A MEALTH HAZARD. SYNTOMS MAY NOT BE INMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION. ------ SECTION V - REACTIVITY DATA ------

STABILITY: STHELE CONDITIONS TO AVOID

INCOMPATIBLEITY (MATERIALS TO AVOID)

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

MAY CAUSE HAZARDOUS FLMES WHEN HEATED TO DECOMPOSITION, FUMES MAY CONTAIN CARBONMONOXIDE, CARBON DIGALDE.

HAZARDOUS POLYMERIZATION: WILL NO: OCCUR

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE IRLIGITION OF THE RESPIRATORY TRACT; HEADACHE, NOUSEA, DIZZINESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE INCASE OF EYE CONTACT, FLUSH WHITH LARSE PROJUNTS OF WATER FOR AT LEAST 15 MINUTES, GET MEDICAL ASSISTANT,

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE REMOVE WHITH SOAP AND MATER. REMOVED SOILED CLOTHING.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

DRINK I OR 2 GLASSES OF MATER DILLTE, DO NOT INDUCE VONITING, CONSULT PHYSICIAN OR POISON CONTROL CENTER IMMENTATELY.
TREAT SYNTOMATICALLY.

HEALTH HAZARDS (ACUTE AND CHRONIC)

PROLONGED AND REPEATED BREATHING OF SPRAY MIST AND/OR SANDING DUST OVER A PERIOD OF YEARS MAY CAUSE OUST DISEASE OF THE LUNGS.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO MONOGRAPHS?

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE NOW WE'D IN ADDRESSION AD

EMERGENCY AND FIRST AID PROCEDURES

IF BREATHED: REMOVED TO FRESH AIR. IF IN EYES:IN CASE OF EYE CONTACT, FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST IS
ALMIES. IF OF SKIN:REMOVE WITH SOAP AND WATER, REMOVED SOLLED CLOTHING. INDESTION: INDUCE VONLING PROMILE ACCORDING
TO PHYSICIANS INTRUCTIONS OR BY HAVING PATIENT STICK FINGER DOWN THROAT. AFTER VONLITING HAS BEEN INDUCED, GIVE TWO TEAS
PROMILES OF BRAING SUAR IN HATER.

======= SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =========

STEPS TO BE FAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

WASH WITH WATER, BEFORE ATTENIONS CLEAN UP, REFER TO HAZARD CAUTION INFORMATION IN OTHER SECTION OF THIS MATERIAL SAFETY
THATA FORM. JUNTAIN SOULED MATERIAL ANDREWOVED WITH THEIR ASSUMENT, STORE IN CLOSED CONTRINER.

WASYE DISPOSAL METHOD

DISPOSE UF IN HEDROANCE WITH LOCAL. STATE AND FEDERAL REBULATION.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE BELOW 180 F AND KEEP FROM FREEZING. KEEP CONTRINER CLOUSED WHEN NOT IN USEDO NOT REUSE EMPTY CONTRINER. WEEP OUT OF REALTH OF CATA DREN.

OTHER PRECAUTIONS

NUME

RESPIRATORY PROTECTION

DO NOT BREATHE VAPORS, SPRAY MIST OR SANDING DUST. WHEN SPRAY APPLIED IN OUTDOOR OR OPEN AREASMITH UNRESTRICTED VENTILA-ION, AND DURING SANDINGOR GRINDING OPERATION, USE MIOSH/MSHA APROVED MACHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRS DRNE PARTICLES OF OVERSPRAY AND SANDING DUST.

VENTILATION

USE ONLY WITH ADEQUATE VENTICATION, PROVIDE GENERAL DILUTION OR LOCAL EXHAUST — VENTICATION IN VOLUME AND PATTERN TO KEEP AIR CUIRININGNI CONCERNATION BELOW CURRENT APPLICABLE SAFETY AND HEALTH STANDARS IN THE MIXING.

PROTECTIVE GLOVES

NÚT REGUÍRED.

EYE PROTECTION

DO NOT IN EYES. SAFETY EYEMEAR WITH SPLASH GUARDS OR RECOMMENDED TO PREVENT CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NOT REQUIRED.

WORK/HYGIENIC PRACTICES

REMOVE AND WASH STILLED CLOTHING BEFORE REUSE, WASH HANDS BEFORE ERTING, SMOKING OR USING THE BASHROOM.

DISCLAIMER

The information contained merein is based on data believed by this company to be accurate, but we do not assume any itability for its accuracy. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. The manner of that use and whether there is any infringement of patents is the sole responsability of the user.